

CONSTRUCTION METHOD

- >>> Base Yarns Provide overall stability
- >>> Lock Yarns Interlocking device to Lock the Loop
- >>> Pile Yarns Independent Loop construction

A QUALITY PRODUCT BY " STAR CARPET "

INNOVATION & INSPIRATION

MANUFACTURING SPECIFICATIONS

>>> Construction	Woven Interlock
>>> Dye system	100 % Solution Dyed
>>> Yarn Content	100 % BCF Olefin
>>> Yarn We	36 Oz. Per Sq. Yd. (1220 gm/m2)
>>> Gauge	5/32"
>>> Pile Height	4 mm.
>>> Row per inch	6
>>> Secondary Backing	Action Bac
>>> Total weight	88 Oz. Per Sq. Yd. (2985 gm/mm2)

PERFORMANCE SPECIFICATION

>>> A S 1530. 1989 (Australian Standard)	Pass
>>> Smoke Develop Index	4
>>> Color Fastness to Shampoo (AS 2111.19.2)	4 (Good)
>>> Color Fastness To Light	More than 5 (Very Good)
>>> Static Control	Built - in - Permanent
>>> Wear Warranty	10 Years Limited Warranty

RECOMMENDED USAGE

These fabrics are designed for all commercial traffic applications when install utilizing CRI 104 installation techniques. Such applications are include business and Doctor's offices, stores, restuarants, and residential recreation rooms.



- Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication of finishing, and may vary in vary within normal industry tolerances. Performance is not affected by these variables.
- As in all qualities carpets, colors are subject to dye lot variations. Shading is the result of Pile reversal and often times are described as " watermarking ". Since this is an optical characteristic of cut pile and cut / loop carpet, it does not constitute a manufacturing defect.
- Chair pads are required under roller caster to prevent accelerated wear.



STAR CARPET CO.,LTD. : Carpets, Carmats, Doormats, Innovation
Sales Thailand : 66 44 212 705 - 6. Fax : 66 44 212 708.

starex@starmanufacturing.co.th

www.starcarpet.co.th